

Rotary tiller for home use


195



Ideal for home gardeners who need to soften up the soil for seeding, this model offers an excellent combination of manageability and user-friendliness.



Front wheel for easy transportation of the machine. The wheel can be easily folded upward without tools to facilitate operations on the ground.



Handlebars with horizontal and vertical adjustment to allow the operator to assume the correct posture while working.



82 cm rotor with three elements per side with lateral protection discs.

Power supply	Engine	Model	Displacement	Power*	Starting	Code
gasoline	Emak	K 800 HT OHV	182 cm ³	5.7 HP	recoil start	68599001EN

* Engine power data refers to the values declared by each manufacturer. These values are calculated in accordance with specific measurement standards (such as SAE J1940, SAE J1349, ISO 1585) and may be modified without prior notice.

Focus on accessories



Furrowing tool
Code **69209081**
(requires tool holder **69209087**)



Plough
Code **69209082**
(requires tool holder **69209087**)



Potato digger
Code **69209083**
(requires tool holder **69209087**)



Pair of metal wheels
Code **69209084**




Gearbox/ Speed (km/h):

2-speed (1 forward + 1 reverse)

Speed (km/h) 8.40 1 1R 3.50

Rotor speed with engine at 3400 rpm 159 1 1R 66

Dimensions (mm)



L1	1400
H1	800
W1	820

Transmission	chain
Clutch	belt with tensioner
Handlebars	with vertical and horizontal adjustment
Rotor	82 cm with lateral protection discs
Power take-off	no
Jackleg	yes
Towing hitch	yes
Transport wheel	yes
Weight	60 kg